UHF PCB ANTI-METAL TAG

- Product Specifications -



- **Model:** RS-PT3613
- **Material:** FR-4 (PCB)
- **Frequency:** (US) 902-928MHz
- **Size:** 36x13mm, (Hole: D2.0mmx2)
- **Chip:** Alien Higgs-3
- **Protocol:** EPC Class1 Gen2, ISO18000-6C
- **Reading Range:** UP to 4.7m (based on reader/writer and installation method)
- **Read/Write Times:** ≥100,000 times
- **Operating Temperature:** -40℃~100℃
- **Certifications:** Reach Approved, RoHS Approved, CE Approved

Product Description

RS-PT3613 is a UHF RFID tag for hospital asset tracking, including medications, tools, and equipment. It helps reduce asset loss, cut search time, provide real-time usage data, monitor storage conditions, and plan maintenance. Measuring 36×13×3.5mm and weighing 3.5g, it offers a read range of up to 4.7 meters.

Technical Parameters

Physical Characteristics	
Material	FR-4 (PCB)
Size	36x13mm, (Hole: D2.0mmx2)
Thickness	3.5mm
Color	Black (Red, Blue, Green, White)
Storage Temperature	-40~+150℃ (-40~302℉)
Operation Temperature	-40~+100℃ (-40~212℉)
Electrical Characteristics	
Frequency	(US) 902-928MHz
Chip Type	Alien Higgs-3
Memory	EPC 96bits (Up to 480bits) , USER 512bits, TID64bits
Read/Write Times	≥100,000 times
Data Storage	10 years
Reading Distance *The final read range depends on RFID Reading equipment and application environment.	Up to 4.7 m (depending on the tool and the depth of insertion into the slot; based on the example of being embedded in a metal surface with no metal obstruction)

Key Features

- Sturdy and durable;
- Metal-resistant;
- High-temperature resistant;
- Corrosion-resistant;
- Adhesive or Screw-Mounted;
- IP68 Waterproof.

Application


For metal asset management & tracking, IOT & inventory management, etc..






Performance

Frequency: (US) 902-928MHz





CONTACT

Ms. Edith Chen

P/W: +86 13612933572
Email: info@rfidsilicone.com
Skype: live:cxjrfid

ADD: 4th Floor, Building B, Phase 1, Longzhixiang Tiancheng Sci-Tech Park, No.27-5 Tiancheng Road, Longhua District, Shenzhen, China 518100